

SKU: 237.00002



Light Colour	<u>N/A</u>
Power Rating (W)	<u>N/A</u>
Light Angle	<u>N/A</u>
Beam Angle	<u>N/A</u>
Colour (Body)	<u>White</u>
Lumens	<u>N/A</u>
Tension (V)	<u>100-250</u>
CRI	<u>N/A</u>
IP	<u>20</u>
Lumen maintenance (hour)	<u>N/A</u>
Inclination Angle	<u>45</u>
Rotation Angle	<u>0</u>
MacAdam Step	<u>N/A</u>
Zhaga	<u>N</u>
Double Insulation	<u>Y</u>
Tiple Insulation	<u>N</u>
Cross	<u>N</u>
Barn Door	<u>N</u>
Honeycomb Louver	<u>N</u>
Miro Reflector	<u>N</u>
Wall Washer	<u>N/A</u>
Snoot	<u>N</u>
Glass	<u>Y</u>
Dimmable	<u>N/A</u>
Projector Measurement (mm)	<u>Ø89x45</u>
Projector Weight (kg)	<u>0.1</u>
Projector Box Size (mm)	<u>100x100x50</u>

PRODUCT DESCRIPTION

Ceiling-recessed luminaire with aluminum body and optional rubber for IP54 rating. Small simple round design with orientable GU10 socket for LED Lamp. Special body colour, light colour or power available under request.

[print_product id="PRODUCT_ID" mode="pdf" show_icon="no" text="DataSheet Product PDF"]

[Energetic certificate - EPREL](#)

[Declaration of Conformity](#)