

SKU: 233.41652



Light Colour	<u>Neutral White</u>
Power Rating (W)	<u>16</u>
Light Angle	<u>Wide</u>
Beam Angle	<u>41</u>
Colour (Body)	<u>White</u>
Lumens	<u>1500</u>
Tension (V)	<u>100-250</u>
CRI	<u>90</u>
IP	<u>20</u>
Lumen maintenance (hour)	<u>40000</u>
Inclination Angle	<u>0</u>
Rotation Angle	<u>0</u>
MacAdam Step	<u>3</u>
Zhaga	<u>N</u>
Double Insulation	<u>Y</u>
Tiple Insulation	<u>N</u>
Cross	<u>N</u>
Barn Door	<u>N</u>
Honeycomb Louver	<u>N</u>
Miro Reflector	<u>Y</u>
Wall Washer	<u>N</u>
Snoot	<u>N</u>
Glass	<u>Y</u>
Dimmable	<u>Y</u>
Projector Measurement (mm)	<u>100x100x122</u>
Projector Weight (kg)	<u>0.35</u>
Projector Box Size (mm)	<u>160x160x190</u>

PRODUCT DESCRIPTION

Ceiling-recessed luminaire with aluminum body. Modern small square anti-glare design, with fixed LED engine. Special body colour, light colour or power available under request.

[print_product id="PRODUCT_ID" mode="pdf" show_icon="no" text="DataSheet Product PDF"]

Energetic certificate - EPREL

Declaration of Conformity