**SKU:** 202.41231





| | |
|---|---|
| **Light Colour** | Neutral White |
| **Power Rating (W)** | 12 |
| **Light Angle** | Flood |
| **Beam Angle** | 24 |
| **Colour (Body)** | Black |
| **Lumens** | 960 |
| **Tension (V)** | 100-250 |
| **CRI** | 90 |
| **IP** | 20 |
| **Lumen maintenance (hour)** | 35000 |
| **Inclination Angle** | 20 |
| **Rotation Angle** | 0 |
| **MacAdam Step** | 3 |
| **Zhaga** | N |
| **Double Insulation** | Y |
| **Tiple Insulation** | N |
| **Cross** | N |
| **Barn Door** | N |
| **Honeycomb Louver** | N |
| **Miro Reflector** | Y |
| **Wall Washer** | N |
| **Snoot** | N |
| **Glass** | Y |
| **Dimmable** | Y |
| **Projector Measurement (mm)** | Ø90×80 |
| **Projector Weight (kg)** | 0.4 |
| **Projector Box Size (mm)** | 110x100x100 |

**PRODUCT DESCRIPTION**

Ceiling-recessed luminaire with aluminum body. Small simple round design with orientable LED engine.
Special body colour, light colour or power available under request.

[print_product id="PRODUCT_ID" mode="pdf" show_icon="no" text="DataSheet Product PDF"]

Energetic certificate - EPREL

Declaration of Conformity