

**SKU:** 209.34051



<b>Light Colour</b>	<u>Warm White</u>
<b>Power Rating (W)</b>	<u>40</u>
<b>Light Angle</b>	<u>Wide</u>
<b>Beam Angle</b>	<u>46</u>
<b>Colour (Body)</b>	<u>Black</u>
<b>Lumens</b>	<u>3600</u>
<b>Tension (V)</b>	<u>100-250</u>
<b>CRI</b>	<u>90</u>
<b>IP</b>	<u>20</u>
<b>Lumen maintenance (hour)</b>	<u>40000</u>
<b>Inclination Angle</b>	<u>30</u>
<b>Rotation Angle</b>	<u>355</u>
<b>MacAdam Step</b>	<u>3</u>
<b>Zhaga</b>	<u>Y</u>
<b>Double Insulation</b>	<u>Y</u>
<b>Tiple Insulation</b>	<u>N</u>
<b>Cross</b>	<u>Y</u>
<b>Barn Door</b>	<u>Y</u>
<b>Honeycomb Louver</b>	<u>Y</u>
<b>Miro Reflector</b>	<u>Y</u>
<b>Wall Washer</b>	<u>Y</u>
<b>Snoot</b>	<u>N</u>
<b>Glass</b>	<u>Y</u>
<b>Dimmable</b>	<u>Y</u>
<b>Projector Measurement (mm)</b>	<u>Ø155x90</u>
<b>Projector Weight (kg)</b>	<u>1.15</u>
<b>Projector Box Size (mm)</b>	<u>170x170x160</u>

**PRODUCT DESCRIPTION**

Ceiling-recessed luminaire with aluminium body. Round shaped slim design with tilting LED engines. Special body colour, light colour or power available under request.

[print\_product id="PRODUCT\_ID" mode="pdf" show\_icon="no" text="DataSheet Product PDF"]

Energetic certificate - EPREL

Declaration of Conformity