

SKU: 214.32011



| | |
|-----------------------------------|--------------------|
| Light Colour | <u>Warm White</u> |
| Power Rating (W) | <u>40</u> |
| Light Angle | <u>Spot</u> |
| Beam Angle | <u>16</u> |
| Colour (Body) | <u>Black</u> |
| Lumens | <u>3600</u> |
| Tension (V) | <u>100-250</u> |
| CRI | <u>90</u> |
| IP | <u>20</u> |
| Lumen maintenance (hour) | <u>40000</u> |
| Inclination Angle | <u>70</u> |
| Rotation Angle | <u>355</u> |
| MacAdam Step | <u>3</u> |
| Zhaga | <u>Y</u> |
| Double Insulation | <u>Y</u> |
| Tiple Insulation | <u>N</u> |
| Cross | <u>Y</u> |
| Barn Door | <u>Y</u> |
| Honeycomb Louver | <u>Y</u> |
| Miro Reflector | <u>Y</u> |
| Wall Washer | <u>Y</u> |
| Snoot | <u>N</u> |
| Glass | <u>Y</u> |
| Dimmable | <u>Y</u> |
| Projector Measurement (mm) | <u>275x140x68</u> |
| Projector Weight (kg) | <u>1.5</u> |
| Projector Box Size (mm) | <u>290x260x130</u> |

PRODUCT DESCRIPTION

Ceiling-recessed luminaire with aluminium body. Round shaped slim design with tilting LED engines. Special body colour, light colour or power available under request.

[print_product id="PRODUCT_ID" mode="pdf" show_icon="no" text="DataSheet Product PDF"]

Energetic certificate - EPREL

Declaration of Conformity