

SKU: 215.44031



| | |
|-----------------------------------|---------------|
| Light Colour | Neutral White |
| Power Rating (W) | 40 |
| Light Angle | Flood |
| Beam Angle | 23 |
| Colour (Body) | Black |
| Lumens | 3600 |
| Tension (V) | 100-250 |
| CRI | 90 |
| IP | 20 |
| Lumen maintenance (hour) | 40000 |
| Inclination Angle | 30 |
| Rotation Angle | 360 |
| MacAdam Step | 3 |
| Zhaga | Y |
| Double Insulation | Y |
| Tiple Insulation | N |
| Cross | N |
| Barn Door | N |
| Honeycomb Louver | Y |
| Miro Reflector | Y |
| Wall Washer | N |
| Snoot | N |
| Glass | Y |
| Dimmable | Y |
| Projector Measurement (mm) | Ø165x150 |
| Projector Weight (kg) | 1.2 |
| Projector Box Size (mm) | 200x170x175 |

PRODUCT DESCRIPTION

Ceiling-recessed luminaire with aluminum body. Round anti-glare design with orientable LED engine. Special body colour, light colour or power available under request.

[print_product id="PRODUCT_ID" mode="pdf" show_icon="no" text="DataSheet Product PDF"]

Energetic certificate - EPREL

Declaration of Conformity