

SKU: 233.41652



| | |
|-----------------------------------|----------------------|
| Light Colour | <u>Neutral White</u> |
| Power Rating (W) | <u>16</u> |
| Light Angle | <u>Wide</u> |
| Beam Angle | <u>41</u> |
| Colour (Body) | <u>White</u> |
| Lumens | <u>1500</u> |
| Tension (V) | <u>100-250</u> |
| CRI | <u>90</u> |
| IP | <u>20</u> |
| Lumen maintenance (hour) | <u>40000</u> |
| Inclination Angle | <u>0</u> |
| Rotation Angle | <u>0</u> |
| MacAdam Step | <u>3</u> |
| Zhaga | <u>N</u> |
| Double Insulation | <u>Y</u> |
| Tiple Insulation | <u>N</u> |
| Cross | <u>N</u> |
| Barn Door | <u>N</u> |
| Honeycomb Louver | <u>N</u> |
| Miro Reflector | <u>Y</u> |
| Wall Washer | <u>N</u> |
| Snoot | <u>N</u> |
| Glass | <u>Y</u> |
| Dimmable | <u>Y</u> |
| Projector Measurement (mm) | <u>100x100x122</u> |
| Projector Weight (kg) | <u>0.35</u> |
| Projector Box Size (mm) | <u>160x160x190</u> |

PRODUCT DESCRIPTION

Ceiling-recessed luminaire with aluminum body. Modern small square anti-glare design, with fixed LED engine. Special body colour, light colour or power available under request.

[print_product id="PRODUCT_ID" mode="pdf" show_icon="no" text="DataSheet Product PDF"]

Energetic certificate - EPREL

Declaration of Conformity