
**SKU:** 238.32062



| | |
|---|---|
| **Light Colour** | Warm White |
| **Power Rating (W)** | 20 |
| **Light Angle** | Very-wide |
| **Beam Angle** | 90 |
| **Colour (Body)** | White |
| **Lumens** | 1840 |
| **Tension (V)** | 100-250 |
| **CRI** | 90 |
| **IP** | 20 |
| **Lumen maintenance (hour)** | 30000 |
| **Inclination Angle** | 0 |
| **Rotation Angle** | 360 |
| **MacAdam Step** | 3 |
| **Zhaga** | N |
| **Double Insulation** | Y |
| **Tiple Insulation** | Y |
| **Cross** | N/A |
| **Barn Door** | N/A |
| **Honeycomb Louver** | N/A |
| **Miro Reflector** | N/A |
| **Wall Washer** | N/A |
| **Snoot** | N/A |
| **Glass** | N |
| **Dimmable** | N |
| **Projector Measurement (mm)** | Ø180×55 |

**PRODUCT DESCRIPTION**

Aluminum die casting downlight with simple round design.Very wide light spread for homogeneous lighting.Suitable for replace fluorescent downlight with higher lumen output and lifespan.

[print_product id="PRODUCT_ID" mode="pdf" show_icon="no" text="DataSheet Product PDF"]

Energetic certificate - EPREL

Declaration of Conformity