

SKU: 238.32062



| | |
|-----------------------------------|------------|
| Light Colour | Warm White |
| Power Rating (W) | 20 |
| Light Angle | Very-wide |
| Beam Angle | 90 |
| Colour (Body) | White |
| Lumens | 1840 |
| Tension (V) | 100-250 |
| CRI | 90 |
| IP | 20 |
| Lumen maintenance (hour) | 30000 |
| Inclination Angle | 0 |
| Rotation Angle | 360 |
| MacAdam Step | 3 |
| Zhaga | N |
| Double Insulation | Y |
| Tiple Insulation | Y |
| Cross | N/A |
| Barn Door | N/A |
| Honeycomb Louver | N/A |
| Miro Reflector | N/A |
| Wall Washer | N/A |
| Snoot | N/A |
| Glass | N |
| Dimmable | N |
| Projector Measurement (mm) | Ø180x55 |

PRODUCT DESCRIPTION

Aluminum die casting downlight with simple round design. Very wide light spread for homogeneous lighting. Suitable for replace fluorescent downlight with higher lumen output and lifespan.

[print_product id="PRODUCT_ID" mode="pdf" show_icon="no" text="DataSheet Product PDF"]

Energetic certificate - EPREL

Declaration of Conformity