SKU: 401.32032





Light Colour	Warm White
Power Rating (W)	20
Light Angle	Flood
Beam Angle	22
Colour (Body)	White
Tension (V)	100-250
CRI	90
IP	20
Lumen maintenance (hour)	40000
Inclination Angle	90
Rotation Angle	355
MacAdam Step	3
Zhaga	Y
Double Insulation	Y
Cross	N
Barn Door	Y
Honeycomb Louver	Y
Miro Reflector	Y
Wall Washer	Y
Glass	Y
Dimmable	Y
Projector Measurement (mm)	Ø88×116
Projector Weight (kg)	1.2
Projector Box Size (mm)	225x180x100
Efficiency	105.84
Energy Class	F
ID EPREL	https://eprel.ec.europa.eu/screen/product/lightsources/1596350

PRODUCT DESCRIPTION

20w and 30w track led projector with passive cooler, in aluminium die casting trim can be white or black (other colour under request).
Slick design hides the heat sink for better looking luminaire, which can be 355º rotatable and 90º tiltable.
Reflector Made of 99.98% Aluminium with front ring made of high temperature resistant PC material. The oxidized finished heat sink strengthens the cooling of fixture.
LED Module mounting hole dimension meets the standard of zhaga.

[print_product id="PRODUCT_ID" mode="pdf" show_icon="no" text="DataSheet Product PDF"]

Energetic certificate - EPREL

Declaration of Conformity