

SKU: 401.33012





| Light Colour | Warm White |
|----------------------------|--|
| Power Rating (W) | 30 |
| Light Angle | Spot |
| Beam Angle | <u>16</u> |
| Colour (Body) | White |
| Tension (V) | 100-250 |
| CRI | 90 |
| IP | 20 |
| Lumen maintenance (hour) | 40000 |
| Inclination Angle | 90 |
| Rotation Angle | <u>355</u> |
| MacAdam Step | 3 |
| Zhaga | Y |
| Double Insulation | Y |
| Cross | N |
| Barn Door | Y |
| Honeycomb Louver | Y |
| Miro Reflector | Y |
| Wall Washer | Y |
| Glass | Y |
| Dimmable | Y |
| Projector Measurement (mm) | Ø88×116 |
| Projector Weight (kg) | 1.2 |
| Projector Box Size (mm) | 225x180x100 |
| Efficiency | 105.84 |
| Energy Class | E |
| ID EPREL | https://eprel.ec.europa.eu/screen/product/lightsources/1596371 |



PRODUCT DESCRIPTION

20w and 30w track led projector with passive cooler, in aluminium die casting trim can be white or black (other colour under request).

Slick design hides the heat sink for better looking luminaire, which can be 355° rotatable and 90° tiltable. Reflector Made of 99.98% Aluminium with front ring made of high temperature resistant PC material. The oxidized finished heat sink strengthens the cooling of fixture.

LED Module mounting hole dimension meets the standard of zhaga.

[print_product id="PRODUCT_ID" mode="pdf" show_icon="no" text="DataSheet Product PDF"]

Energetic certificate - EPREL

Declaration of Conformity