

**SKU:** 414.33012



<b>Light Colour</b>	Warm White
<b>Power Rating (W)</b>	30
<b>Light Angle</b>	Spot
<b>Beam Angle</b>	19
<b>Colour (Body)</b>	White
<b>Tension (V)</b>	100-250
<b>CRI</b>	90
<b>IP</b>	20
<b>Lumen maintenance (hour)</b>	40000
<b>Inclination Angle</b>	90
<b>Rotation Angle</b>	355
<b>MacAdam Step</b>	3
<b>Zhaga</b>	N
<b>Double Insulation</b>	Y
<b>Cross</b>	N
<b>Barn Door</b>	N
<b>Honeycomb Louver</b>	N
<b>Miro Reflector</b>	Y
<b>Wall Washer</b>	N
<b>Snoot</b>	N
<b>Glass</b>	Y
<b>Dimmable</b>	Y
<b>Projector Measurement (mm)</b>	Ø80x155
<b>Projector Weight (kg)</b>	0.75
<b>Projector Box Size (mm)</b>	265x225x115
<b>Efficiency</b>	98
<b>Energy Class</b>	E
<b>ID EPREL</b>	<a href="https://eprel.ec.europa.eu/screen/product/lightsources/1596103">https://eprel.ec.europa.eu/screen/product/lightsources/1596103</a>

**PRODUCT DESCRIPTION**

Track luminaire with aluminum body. Modern and stylish design with power supply integrated in the track power feeder and orientable LED engine in any direction.  
Special body colour, light colour or power available under request.

[print\_product id="PRODUCT\_ID" mode="pdf" show\_icon="no" text="DataSheet Product PDF"]

[Energetic certificate - EPREL](#)

[Declaration of Conformity](#)